

**Keep peace with  
your budget.**

# Peacekeeper

## Water Softener

### Simple as One, Two, Three

Set the time, salt dosage, and hardness then your ready for operation.

### Efficiency and Reliability:

Internal meter automatically initiates regeneration, and a 7 day override for reliable performance.

### Easy to Retrieve Performance Data:

Controller tracks total water used, days and water since last regeneration, and average water usage for every day of the week.

### Time Proven Valve Design:

Camshaft & Flapper design provides years of trouble free operation.

### Large Salt Storage Tank:

Holds enough salt for up to 12 regenerations, reducing the frequency of salt handling trips.

### Bypass Assembly Included:

For easy installation and maintenance.

### Basic Installation Kit:

Components for most simple installations are included.



Tested and Certified by WQA to NSF/  
ANSI Standard 44 & 372 for softener  
performance & lead free compliance and  
CSA B483.1.

C USA



| Model   | Media Tank Size | Resin Volume         | Rated Flow @ Pressure Drop | Brine Tank | Salt Storage | Drain Flow | Inlet/Outlet | Drain    | Brine    | Ship Weight |
|---------|-----------------|----------------------|----------------------------|------------|--------------|------------|--------------|----------|----------|-------------|
| DRS8-26 | 8"x44"          | 0.80 ft <sup>3</sup> | 8gpm @ 12psi               | 14"x34"    | 240 lbs      | 1.7 gpm    | 1" NPT       | 1/2" NPT | 3/8" NPT | 78 lbs      |
| DRS8-34 | 9"x44"          | 1.04 ft <sup>4</sup> | 9.6gpm @ 15psi             | 14"x34"    | 240 lbs      | 2.1 gpm    | 1" NPT       | 1/2" NPT | 3/8" NPT | 95 lbs      |
| DRS8-40 | 10"x44"         | 1.25 ft <sup>5</sup> | 10.7gpm @ 15psi            | 14"x34"    | 240 lbs      | 2.7 gpm    | 1" NPT       | 1/2" NPT | 3/8" NPT | 110 lbs     |

**Large LED Display**

- Highly Visible in most installations.

**Camshaft Indicator**

- Provides a visual indicator of the camshaft rotation.

**Manual Regeneration Button**

- Initiates either immediate or delayed regeneration.

**Time Button**

- Displays current hour of the day and allows for easy time adjustments.

**Salt Button**

- Sets or Displays the current salt setting (high efficiency/high capacity).

**Hardness Button**

- Sets or Displays the incoming water hardness.

**Flow Indicator**

- Blinks on and off when water flow is present.

**Power Loss Memory Retention**

- Features battery-free Time of Day retention during loss of power. All other parameters are permanently retained in flash memory.

**7 Cycle Regeneration:**

- Backwash, Brine Draw, Repressurize, Rinse, 2nd Backwash, 2nd Rinse, Fill..

| Dim       | DRS8-26     | DRS8-34     | DRS8-40     |
|-----------|-------------|-------------|-------------|
| A         | 48.3"       | 52.33"      | 48.4"       |
| B         | 46.5"       | 50.51"      | 46.6"       |
| C         | 24.36"      | 25.36"      | 26.36"      |
| Footprint | 25"W x 15"D | 25"W x 15"D | 26"W x 15"D |

